

U.S. Battery Proudly Introduces Our Brand New Line of Advanced **AGM** 6 & 12 volt batteries.



Golf Carts
Electric Vehicle
Renewable Energy
Solar Power Systems
Wind & Hydro Power Systems
Aerial Lift and Access Equipment

Marine & RV
Floor Machines
Military Ordnance



Home Medical Equipment (HME)
Uninterrupted Power Supplies (UPS)
AGM uses are practically unlimited. . .

All of U.S. Battery's AGM Batteries feature the latest and most advanced paste and plate making technologies available. **Our Premium AGM Batteries are Sealed, and Maintenance Free. They are Spill Proof, will not leak and can withstand most freezing temperatures.**



U.S. Battery's AGM products offer several advantages over both conventional flooded and GEL lead acid battery types. Since the acid (electrolyte) is absorbed in glass-mats (AGM) surrounding the plates, they will not spill if broken. In addition, since there is no free liquid to cause damage if frozen, our AGM Batteries are rarely damaged by freezing temperatures. Heat generation is reduced during the charge and discharge cycle, providing you longer and more reliable life cycles. All of U.S. Battery's AGM products have very low self discharge rates allowing our batteries to be stored for longer periods of time without the need to boost charge as often. Hydrogen gas emission is less than 4%, allowing U.S. Battery's AGM products to be used in applications and in areas with enclosed spaces (but not in sealed or gas-tight containers)

U.S. Battery's AGM plates are constructed and rigidly mounted while tightly packed to withstand shock and vibration found in many motive power applications giving you years of **Reliable, Dependable** and **Maintenance Free** usage

U.S. BATTERY SEAL-ED **AGM**



See our entire line of Premium Deep Cycle Batteries at: www.usbattery.com

AGM SPECIFICATIONS





6 Volt Sealed AGM

Type	20 HR rate	5 HR rate	Min of Discharge @75 Amps	Min of Discharge @56 Amps	Min of Discharge @25 Amps	CCA@ 0°F -18°C	CA@ 32°F 0°C	Length	Width	Height
US AGM 2000	210	185	120	182	450	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	226	149	228	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)
US AGM 305	312	271	208	295	736	720	865	11.61" (295mm)	7.09" (180mm)	14.41" (366mm)
US AGM L16	390	331	255	374	915	730	875	11.61" (295mm)	7.09" (180mm)	16.85" (428mm)
US AGM 6V27	214	180	-	-	450	900	1000	12.05" (306mm)	6.61" (168mm)	9.98" (228mm)

12 Volt Sealed AGM

US AGM 185	234	198	125	191	518	775	930	15.24" (387mm)	7.09" (180mm)	14.49" (368mm)
US AGM 31	100	N/A	52	-	190	800	960	13.00" (330mm)	6.85" (174mm)	9.37" (238mm)
US AGM U1	35	29.7	-	-	45	240	280	7.68" (195mm)	5.12" (130mm)	7.09" (180mm)



US AGM



See our entire line of Premium Deep Cycle Batteries at: www.usbattery.com