

MARINE

# Diamond Plate Technology®

The New Standard in Battery Power and Cycle life.



## XG ADVANTAGES:

- X Higher Peak Capacity
- X Increased Initial Capacity
- X Improved Energy Density
- X Enhanced Recharge-ability
- X Fortified Plate Construction
- X Improved Cycle Life

**New!**

**New!**

**New!**

8 Volt  
19-4-1

8 Volt  
17-4-1

8 Volt  
15-4-1

8 Volt  
13-4-1

8 Volt  
11-4-1

12 Volt  
31 DCXC

6 Volt  
USAGM250



1675 Sampson Ave.  
Corona, CA 92879  
(800) 695-0945

1895 Tobacco Road  
Augusta, GA 30906  
(800) 522-0945

717 North Blair Rd.  
Evans, GA 30809  
(888) 811-0945

[www.usbattery.com](http://www.usbattery.com)



# For The Extreme Marine Always Demand U.S. Battery's *Diamond Plate Technology*® Batteries



U.S. Battery Manufacturing Company is proud to introduce its breakthrough technology! With "Diamond Plate Technology"™ we are providing you with the highest rated batteries available today. Not only will they out perform the competition, they will last longer and provide you with improved charging profiles, saving both time and money. Don't wait any longer, power up with the **XC** Xtreme Capacity™ advantage today!

## 8 Volt Marine

Type	20 HR rate	5 HR rate	Min @ 75 Amps	Min @ 25 Amps	Length	Width	Height	Weight lbs.	Pallet QTY
11-4-1 XC	145	-	101	323	19-1/4" (489mm)	7-1/2" (191mm)	10-3/4" (273mm)	92.3	24
13-4-1 XC	170	-	116	380	21-7/16" (555mm)	7-1/2" (191mm)	10-1/2" (267mm)	100.6	24
15-4-1 XC	195	-	133	440	24-3/8" (619mm)	7-1/16" (189mm)	10-1/2" (267mm)	117.4	16
17-4-1 XC	220	-	147	490	27-1/16" (689mm)	7-1/16" (189mm)	10-1/2" (267mm)	129.5	16
19-4-1 XC	245	-	162	545	26-3/4" (679mm)	8-7/16" (216mm)	11-1/8" (282mm)	147.9	16

## 12 Volt Marine

US 12V XC	155	122	77	292	13-1/8" (333mm)	7-1/16" (179mm)	11-3/8" (289mm)	90	36
24 TM	85	-	-	125	10-3/4" (273mm)	6-3/4" (171mm)	9-3/4" (248mm)	47	72
27 DCXC	105	90	42	205	12-3/4" (324mm)	6-3/4" (171mm)	9-3/4" (248mm)	58.6	54
31 DCXC	130	99	49	225	13" (330mm)	6-3/4" (171mm)	9-3/4" (248mm)	65.5	54

## 6 Volt AGM Marine

Type	20 HR rate	5 HR rate	Min of Discharge @75 Amps	Min of Discharge @56 Amps	Min of Discharge @25 Amps	CCA@ 0°F	CA@ 32°F	Length	Width	Height
US AGM 2000	210	185	120	182	450	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	226	149	228	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)
US AGM 305	312	271	208	295	736	720	865	11.61" (295mm)	7.09" (180mm)	14.41" (366mm)
US AGM L16	390	331	255	374	915	730	875	11.61" (295mm)	7.09" (180mm)	16.85" (428mm)

## 12 Volt AGM Marine

US AGM 185	234	198	125	191	518	775	930	15.24" (387mm)	7.09" (180mm)	14.49" (368mm)
US AGM 31	100	N/A	52	N/A	190	800	960	13.00" (330mm)	6.85" (174mm)	9.37" (238mm)

**FEATURES:**

**Diamond Plate Technology**® - Advanced paste formulation maximize's capacity life and recharge-ability.

**Antinium**™ - This special grid metal mixture is used to reduce grid corrosion and water usage. In combination, these features will extend the life of your battery by 15-20%.

**Crystalock**™ - Our advanced plate curing process insures structural strength and solid adhesion to the grid, the key to superior cycle life.

**SpeedCap**™ - A positive locking cap that will not vibrate off or "spit" acid when removed. The "gang" feature allows for easy removal of all three caps at once saving time and money.

**Thicker Plates** - Our plates are the thickest in the business, assuring you the longest cycle life possible.

**Extra Electrolyte** - Using shorter, thicker plates allows for more electrolyte over the plates, extending required water intervals.

**Lifting Handle** - Makes installation and removal quick, easy and safe.



12 Volt  
US 31DCXC

WWW.U.S.BATTERY.COM